

# GSM/GRRS Module



# SIM900A

SIMCom presents an ultra compact and reliable wireless module. The SIM900A is a complete Dual-band GSM/GPRS module in a SMT type which is designed specially for Chinese mainland market, allowing you to benefit from small dimensions and cost-effective solutions.

Featuring an industry-standard interface, the SIM900A delivers GSM/GPRS 900/1800MHz performance for voice, SMS, Data, and Fax in a small form factor and with low power consumption. With a tiny configuration of 24mm x 24mm x 3 mm, SIM900A can fit almost all the space requirements in your applications, especially for slim and compact demand of design.

## **Smart Machine Smart Decision**

#### **General features**

- •Dual-Band 900/ 1800 MHz
- •GPRS multi-slot class 10/8
- •GPRS mobile station class B
- •Compliant to GSM phase 2/2+
- Class 4 (2 W @900 MHz)
- Class 1 (1 W @ 1800MHz)
- •SAIC (Single Antenna Interference Cancellation) support
- •Dimensions: 24\* 24 \* 3 mm
- •Weight: 3.4g
- •Control via AT commands (GSM 07.07 ,07.05 and SIMCOM enhanced AT Commands)
- •SIM application toolkit
- •Supply voltage range: 3.2 ... 4.8V
- •Low power consumption: 1.0mA(sleep mode&BS-PA-

MFRMS=9)

•Operation temperature: -40° C to +85° C

#### **Specifications for Fax**

•Group 3, class 1

## **Specifications for GPRS Data**

- •GPRS class 10: max. 85.6 kbps (downlink)
- PBCCH support
- •Coding schemes CS 1, 2, 3, 4
- •PPP-stack

### **Specifications for CSD Data**

- •CSD up to 14.4 kbps
- •USSD
- •Non transparent mode

## Specifications for SMS via GSM/GPRS

- Point to point MO and MT
- •SMS cell broadcast
- •Text and PDU mode

#### **Software features**

- •0710 MUX protocol
- •embedded TCP/UDP protocol
- •FTP/HTTP

#### Customized features

- •FOTA
- •MMS
- Embedded AT

#### **Specifications for Voice**

- Tricodec
- Half rate (HR)
- Full rate (FR)
- Enhanced Full rate (EFR)
- AMR
- Half rate (HR)
- Full rate (FR)
- •Hands-free operation
  - (Echo suppression)

#### Interfaces

- •Interface to external SIM 3V/ 1.8V
- Analog audio interface
- •RTC backup
- •SPI interface
- Two Serial interfaces
- Antenna pad
- •I2C
- •GPIO
- •PWM
- •ADC

### Compatibility

•AT cellular command interface

#### **Certifications:**

- ROHS
- TA
- REACH

# More about SIMCom SIM900A Please contact:

Tel: 86-21-32523300 Fax: 86-21-32523301 Email: simcom@sim.com Website: www.sim.com/wm